



Digital Lifestyle Controller



Features:

LCD Display
24 hour clock
20-year backup battery

- On/Off Switch:** Controls power to unit. Loss of power does not affect time or misting program.
- A Button:** Next Screen: This screen changes the display as you navigate through the controller.
- B Button:** Extra Run Cycle: Initiates one mist cycle.
- +▲ Button:** 1. Increases a selected numeric screen value;
2. Navigates values in the Mist Time Screens; and
3. Activates the days for mist cycles.
- ▼ Button:** 1. Decreases a selected numeric value;
2. Navigates values in the Mist Time Screens; and
3. Deactivates the days for mist cycles.
- OK Button:** Used with Mist Time Screens to switch selected values in and out of “change” mode.
- ESC Button:** Used in advanced programming.

How it Works

1. You select the start time (“Mist Time”) for four daily misting cycles.
2. For each day of the week, you set each Mist Time either “on” or “off.” This allows each day to have between zero and four programmed misting cycles.

3. You determine the duration of the misting cycle (“Mist Duration”). This setting controls both programmed and manual misting cycles.

How to set the clock (date & time)

1. Press OK & ESC simultaneously.
2. Arrow down to OTHER.
3. Press OK.
4. Arrow down to CLOCK.
5. Press OK.
6. Use arrow keys to move the black shadow over the item you wish to set.
7. Press OK.
8. Press the arrow up or down key to set value (date, hour or minute).
9. Press OK to save changes.
10. Repeat 6-9 as necessary.
11. Once the clock settings are correct, press ESC twice to return to main screen.

How to Program Mist Times and Run Duration

1. Press On (System On screen will appear).
2. Press Next Screen (Mist Time 1 screen will appear). The value flashing with a black shadow is the Hour value.
3. Press OK to select Hour value (Hour value will flash with no black shadow). Use Up or Down keys to adjust the Hour. Once the Hour value is set, press OK (Hour value will flash with a black shadow). Use the Down key to move to the Minute value (Minute value will flash with a black shadow).
4. Press OK to select the Minute value (Minute value will flash with no black shadow). Use Up or Down keys to adjust the Minute. Once the Minute value is set, press OK

(Minute value will flash with a black shadow). Use the Down key to move to Monday of the Days of the Week value (M will flash with black shadow).

5. Press OK to select the Monday value. (M will flash with no black shadow). To keep Mist Time 1 operative on Monday's, do nothing. To disable Mist Time 1 on Monday's, press the Down key (-- will flash with no black shadow). To move to Tuesday, press OK (T will flash with no black shadow). To keep Mist Time 1 operative on Tuesday's, do nothing. To disable Mist Time 1 on Tuesday's, press the Down key (-- will flash with no black shadow). To move to Wednesday, press OK. Continue these steps until Mist Time 1 preferences have been set for each day of the week. Once Sunday has been set, press OK (M will flash with a black shadow).

6. Press Next Screen (Mist Time 2 screen will appear) Repeat steps 2-6 for Mist Times 2, 3 & 4. After Mist Time 4 has been set, proceed to step 7.

Note: To completely turn off a Mist Time, disable all seven days of the week for that Mist Time.

7. Press Next Screen (Mist Duration screen will appear with no flashing values). Use Up or Down keys to adjust.

8. Press Next Screen (System On screen will appear). If your master unit was manufactured with a float switch, make certain the drum has sufficient liquid and that the Fluid Level reads OK. Controller is now set.

9. Close controller door securely.
Confirm metal lock ring is locked in place.
Secure vinyl cover over outside lip of drum lid.

<https://www.autoflyspraysystems.com>

